












ANCHOR SELECTION

Anchor Type		Base material		Approvals				
		Cracked concrete	Uncracked concrete	European Technical Approval	Seismic assessment	ICC ES Approval	Fire resistance classification	Sprinkler systems
WIT-PE 500 M		✓	✓	✓	✓	✓	✓	
WIT-PE 500 R		✓	✓	✓	✓	✓	✓	
WIT-VM250 M		✓	✓	✓	✓		✓	
WIT-VM250 R		✓	✓	✓	✓		✓	
W-VIZ		✓	✓	✓	✓		✓	
W-VD			✓	✓			✓	
W-FAZ		✓	✓	✓			✓	✓
W-HAZ		✓	✓	✓	✓	✓	✓	✓
W-SA		✓	✓	✓			✓	✓
W-FA			✓	✓		✓	✓	
W-TM			✓	✓				

REBAR	Specification					Anchor size	Page
	Steel, zinc electro plated	Steel, hot-dip	Stainless steel A4 (316)	Highly corrosion resistant steel	Internal thread		
	✓	✓	✓	✓	✓	M8 - M39	68
✓						ø8 - ø40	94
	✓	✓	✓	✓	✓	M8 - M30	120
✓						ø8 - ø32	144
	✓	✓			✓	M8 - M24	168
			✓	✓	✓	M8 - M24	198
	✓	✓	✓	✓	✓	M8 - M24	228
	✓				✓	M8 - M27	246
			✓	✓	✓	M8 - M24	260
	✓					M6 - M20	274
			✓			M8 - M16	288
	✓					ø7.5 - ø16	302
			✓			ø7.5 - ø12	316
	✓	✓				M6 - M20	330
			✓	✓		M6 - M20	344
	✓				✓	M6 - M12	358
			✓		✓	M6 - M12	372

ANCHOR SELECTION

